


Project: Log Cabin Twist



Block Assembly Diagram



Diagram 1




Diagram 2




Diagram 3




Diagram 4




Diagram 5

Materials

- Gold print, red print, dark red print, and beige print scraps

Finished block: 9" square

Cut the Fabrics

From gold print, cut:

- 4—2½x3" rectangles

From red print, cut:

- 4—1½x4" rectangles
- 4—1½x3" rectangles

From dark red print, cut:

- 4—1x5" rectangles

From beige print, cut:

- 4—1½x4½" rectangles
- 4—1½x3½" rectangles

Assemble the Block

1. Sew a red print 1½x3" rectangle to a long edge of a gold print 2½x3" rectangle (Diagram 1). Press the seam allowance toward the gold rectangle.
2. Sew a beige print 1½x3½" rectangle to the right edge of the pieced unit (Diagram 2). Press the seam allowance toward the gold rectangle.
3. Sew a red print 1½x4" rectangle to the bottom edge of the pieced unit (Diagram 3). Press the seam allowance toward the gold rectangle.
4. Sew a beige print 1½x4½" rectangle to the right edge of the pieced unit (Diagram 4). Press the seam allowance toward the gold rectangle.
5. Sew a dark red print 1x5" rectangle to the bottom edge of the pieced unit to complete a block unit (Diagram 5). Press the seam allowance toward the gold rectangle. The pieced block

unit should measure 5" square, including the seam allowances.

6. Repeat steps 1 through 5 to make a total of four block units.
7. Sew together block units in pairs (Block Assembly Diagram). Press the seam allowances in opposite directions. Then join the pairs to make a block. Press the seam allowance in one direction.