

Project: Log Cabin

Materials

- Solid yellow and assorted light and dark print scraps

Finished block: 11" square

Cut the Fabrics

From solid yellow, cut:

- 1—1½" square for position 1

From assorted light prints, cut:

- 1—1½×10½" strip for position 19
- 1—1½×9½" strip for position 18
- 1—1½×8½" strip for position 15
- 1—1½×7½" strip for position 14
- 1—1½×6½" strip for position 11
- 1—1½×5½" strip for position 10
- 1—1½×4½" strip for position 7
- 1—1½×3½" strip for position 6
- 1—1½×2½" strip for position 3
- 1—1½" square for position 2

From assorted dark prints, cut:

- 1—1½×11½" strip for position 21
- 1—1½×10½" strip for position 20
- 1—1½×9½" strip for position 17
- 1—1½×8½" strip for position 16
- 1—1½×7½" strip for position 13
- 1—1½×6½" strip for position 12
- 1—1½×5½" strip for position 9
- 1—1½×4½" strip for position 8
- 1—1½×3½" strip for position 5
- 1—1½×2½" strip for position 4

3. Add the dark print 1½×2½" strip to the block in position 4 (Diagram 3). Continue to press the seam allowances away from the center.

4. Continue sewing the pieces to the block center in a clockwise direction, following the numerical sequence shown in Diagram 4, until you've completed a block (Block Assembly Diagram).



DIAGRAM 1



DIAGRAM 2



DIAGRAM 3





DIAGRAM 4



BLOCK ASSEMBLY DIAGRAM

Assemble the Block

1. Sew together the solid yellow position 1 square with the light print position 2 square to make the block center (Diagram 1). Press the seam allowance toward the solid yellow square.
2. Sew the light print 1½×2½" strip to a long edge (position 3) of the block center (Diagram 2). Press the seam allowance toward the light print strip.