

10" Compound mitersaws: Where value and function meet

BRAND	MODEL	PERFORMANCE RATINGS (1)														MITER SETTINGS				BEVEL SETTINGS		DIMENSIONS, INCHES		CUTTING CAPACITIES, INCHES				LASER POWER SOURCE	NOISE LEVEL, DECIBELS (NO LOAD)	CORD LENGTH, INCHES	WEIGHT, POUNDS	WARRANTY, YEARS (2)	COUNTRY OF ASSEMBLY (3)	SELLING PRICE (4)	
		PRIMARY								SECONDARY						LEFT AND RIGHT DETENTS, DEGREES	DETENT OVERRIDE? (YES, NO)	MAX. ANGLE (LEFT/RIGHT), DEGREES	STOPS, DEGREES	OVERALL DIMENSIONS (WITH EXTENSION WINGS, IF SO EQUIPPED) (W×D×H)	0° BEVEL		45° BEVEL		MAX. DEPTH AT FENCE (3/4" STOCK)										
		MITER				BEVEL				EFFECTIVENESS OF FENCE	QUALITY OF CUT WITH PREMIUM BLADE	QUALITY OF FACTORY BLADE	PORTABILITY	EASE OF CHANGING BLADE	ACCURACY OF LASER						DUST COLLECTION, WITH EQUIPPED BAG	MAX. ANGLE (RIGHT AND LEFT), DEGREES	AT 0° MITER	AT 45° MITER		AT 0° MITER	AT 45° MITER								
		OBSERVED POWER	ACCURACY OF STOPS	EASE OF CHANGING POSITION	RELIABILITY OF LOCK	SCALE READABILITY	ACCURACY OF STOPS	EASE OF CHANGING POSITION	RELIABILITY OF LOCK																										SCALE READABILITY
CHICAGO ELECTRIC	69683	C	B	C	B	B	B	B	B	B	C	C	D	B	B	B	C	45	0, 8, 15, 22.5, 31.6, 45	N	45/0	0, 45	26 ⁷ / ₈ ×21×22 ¹ / ₂	5 ⁷ / ₈	4 ¹ / ₄	6	4 ¹ / ₄	3 ⁷ / ₈	110V	91	72	27	90 days	C	95
CRAFTSMAN	21236	C	B	C	B	B	B	B	B	B	C	C	D	B	B	B	C	45	0, 8, 15, 22.5, 31.6, 38, 45	N	45/0	0, 45	18×21×22 ¹ / ₂	5 ⁷ / ₈	4 ³ / ₈	6	4 ³ / ₈	3 ³ / ₄	Battery	90	75	27	1	C	130
DEWALT	DW713	A	A	A	A	A	A	A	A	B+	A	B+	C	B	B+	N/A	B	52	0, 10, 15, 22.5, 31.6, 45	Y	45/3	0, 45	20×25×22	6 ⁵ / ₁₆	4 ³ / ₈	6 ⁵ / ₁₆	4 ³ / ₈	3 ⁷ / ₈	N/A	89	75	34	3	M	220
HITACHI	C10FCH2	A	A	A	A	A	A	A	A	B+	A	B+	C	A	B-	A	B	52	0, 15, 22.5, 31.6, 45	N	45/0	0, 45	25 ³ / ₄ ×24×21 ³ / ₄	5 ⁷ / ₈	4 ¹ / ₁₆	6	4 ¹ / ₁₆	3 ⁵ / ₈	110V	89	75	27	5	T	170
MAKITA	LS1040	A	A	A	A	A	A	A	A	B+	A	B+	C+	A	A	N/A	A-	50	0, 15, 22.5, 30, 45	N	45/0	0, 45	18×20×21	5 ¹ / ₄	3 ⁹ / ₁₆	5 ¹ / ₄	3 ⁹ / ₁₆	4	N/A	91	88	27	3	T	200
RIDGID	R4112	A-	A	A	A	A	A	A	A	B+	A	B+	C	B	A	A	A-	51	0, 15, 22.5, 31.6, 45	N	48/48	0, 33.9, 45, 48	20×22 ¹ / ₄ ×23 ¹ / ₂	5 ³ / ₄	4	5 ³ / ₄	4	4	110V	90	74	31	3/Life*	C	200
RYOBI	TS1345L	B-	D	D	C	B	B	B	B	C	C	B-	D	A-	A	A	D	47	0, 15, 22.5, 31.6, 45	N	45/0	0, 45	17 ¹ / ₂ ×21×20	5 ⁵ / ₈	3 ⁷ / ₈	5 ³ / ₄	3 ⁷ / ₈	3 ³ / ₁₆	Battery	90	75	21	3	C	120
SKIL	3317	B	D	D	C	B	B	B	B	B	C	B-	D+	B	C	B	D	47	0, 15, 22.5, 31.6, 45	N	47/0	0, 45	37×21×22 ¹ / ₂	5 ¹¹ / ₁₆	4	5 ¹¹ / ₁₆	4	3 ³ / ₄	110V	91	72	25	3	C	150

1. **A** Excellent **D** Poor
B Good **N/A** Not applicable
C Fair

2.(*) Lifetime service upon registration

3. (C) China
(M) Mexico
(T) Taiwan

4. Prices current at time of article production and do not include shipping, where applicable.