

## THE STRAIGHT SPIN ON 12" DISC SANDERS

BRAND	MODEL	PERFORMANCE RATINGS (1)					PLATEN MATERIAL (2)	TYPE OF DISC BRAKE (3)	TABLE				OVERALL DIMENSIONS (W×D×H), INCHES	DUST-COLLECTION PORT DIAMETER, INCHES	STANDARD ACCESSORIES (4)	CORD LENGTH	WEIGHT, LBS	WARRANTY, YEARS	COUNTRY OF ASSEMBLY (5)	SELLING PRICE (6)
		POWER	DUST COLLECTION	EASE OF ADJUSTING TABLE	QUALITY OF MITER GAUGE	EASE OF CHANGING DISCS			DIMENSIONS (D×W), INCHES	MATERIAL (2)	TILT RANGE, UP/DOWN, DEGREES	$\frac{3}{8}$ × $\frac{3}{4}$ " MITER SLOT? (YES/NO)								
DELTA	31-140	B-	A-	B+	C	B	C	M	8 $\frac{3}{8}$ ×17 $\frac{1}{8}$	C	48/48	Y	19 $\frac{1}{4}$ ×17 $\frac{1}{4}$ ×15	2 $\frac{1}{4}$	D,H,M	6'10"	72	5	C	\$250
GRIZZLY	G0702	A	A-	B-	B-	B-	C	A	15 $\frac{1}{2}$ ×14 $\frac{3}{4}$	C	15/45	N	16 $\frac{1}{2}$ ×27×16	2 $\frac{1}{2}$	D,M	5'	84	1	T	415
	G7297	B	A-	C	C	B+	A	N	8 $\frac{1}{4}$ ×17 $\frac{1}{8}$	A	45/45	N	17 $\frac{1}{8}$ ×17 $\frac{1}{2}$ ×14 $\frac{1}{2}$	2	D,M	5'6"	66	1	C	170
JET	JDS-120S	A	A	A	B+	A	S	M	12 $\frac{5}{8}$ ×16 $\frac{1}{2}$	C	15/45	Y	16 $\frac{3}{4}$ ×22×42	4	C,D,F,M,S	6'	100	5	T	560*
RIKON	51-200	B-	A-	B+	C	B	C	M	8 $\frac{3}{8}$ ×17 $\frac{1}{8}$	C	48/48	Y	19 $\frac{1}{4}$ ×17 $\frac{1}{4}$ ×15	2 $\frac{1}{4}$	D,M	6'10"	72	5	C	240
SHOP FOX	W1828	B	A-	C	C	B+	A	N	7×15 $\frac{3}{4}$	C	45/45	N	19 $\frac{1}{2}$ ×16 $\frac{1}{4}$ ×14 $\frac{1}{2}$	2	D,M	6'	68	2	C	256

1. A Excellent    2. (A) Aluminum    3. (A) Automatic    4. (C) Circle-sanding jig    (H) Dust-collection hose    5. (C) China    6. Prices current at time of article production and do not include shipping, where applicable. (\*) Available without stand and filter for \$500 (model JDS-12B)
- B Good            (C) Cast iron            (M) Manual            (D) Sanding disc            (M) Miter gauge            (T) Taiwan
- C Fair                (S) Steel                (N) No brake            (F) Canister filter            (S) Stand