

BIG AND BEEFY: 3-HP ROUTERS HANDLE THE MOST DEMANDING JOBS

MANUFACTURER	MODEL	PERFORMANCE RATINGS (1)														MOTOR SPEEDS (MIN.-MAX.), RPM x 1,000	BASE CONSTRUCTION						ACCESSORIES (5)		NOISE LEVEL, NO LOAD (DECIBELS)		WEIGHT, LBS-OZ	CORD LENGTH	WARRANTY, YEARS	COUNTRY OF ASSEMBLY (6)	SELLING PRICE (7)	
		POWER	RESPONSIVENESS OF ELECTRONIC SPEED CONTROL	ROUTER-TABLE USE			HANDHELD USE								DUST CONTROL (USING INCLUDED DUST HOODS)		TYPE OF BASE (2)	SUBBASE OPENING, INCHES	BASE OPENING W/O SUBBASE, INCHES	GUIDE BUSHING COMPATIBLE? (YES, NO) (3)	COLLET TIGHTENING METHOD (4)	MAX. COLLET TRAVEL, INCHES	NUMBER OF TURRET DEPTH STOPS	STANDARD	OPTIONAL	AT SLOWEST SPEED						AT FASTEST SPEED
				EASE OF CHANGING BITS	EASE OF SETTING BIT HEIGHT	EASE OF USING ROUTER CONTROLS	EASE OF CHANGING BITS	EASE OF SETTING BIT DEPTH	EASE OF USING ROUTER CONTROLS	OVERALL COMFORT AND CONTROL	DEPTH-SCALE ACCURACY	PLUNGE SMOOTHNESS	EASE OF USING PLUNGE LOCK	DEPTH-STOP RELIABILITY																		
BOSCH	1619EVS	A-	A-	B	B+	B	A	A	A	A	A-	A	A	B	B	8-21	P	2 1/32	3 3/4	Y*	1	2 1/16	6	2,4,A,D,W	C,D,E,G,S	74	96	13-6	8'6"	1	X	\$325
DEWALT	DW625	A-	A	B-	C	B	A	B+	A	B+	A	A	B	A	B	8-22	P	3 13/32	2 5/8	Y	1	2 7/16	3	2,4,A,D	E,G,W	73	94	13-12	9'	3	I	300
FESTOOL	OF2200EB	A	A	B+	C-	B	A	A-	A	A	A	A	B-	A	A	10-22	P	3 13/16	3 13/16	Y	1	3 5/32	4	2,A,D	E,G,S	77	96	18-6	13'	3	G	850
HITACHI	M12V2	A	A	B-	B+	C	A-	A	C+	A-	A-	B	A-	B+	B-	8-22	P	3 7/8	3 7/16	Y	1	2 9/16	3	2,4,A,C,D,E,G,W		70	90	15-5	7'6"	5	M	230
MAKITA	RP2301FC	A	A-	B	B-	B	A-	B	A	A	A-	A	B-	B+	NA	9-22	P	2 3/4	2 7/16	Y	1	2 3/4	3	2,4,A,G,W	E	72	91	14-1	8'	1	J	320
MILWAUKEE	5625-20	A	A	A-	A	B+	A	A	B+	A	A	NA	NA	NA	NA	10-22	F	2 1/2	4 1/8	N	2	1 21/32	NA	2,W	4,A,G,S	74	94	12-0	8'	5	C	350
PORTER-CABLE	7518	A-	C	B	B	B-	A	A-	B+	B	A	NA	NA	NA	NA	10,13,16,19,21	F	1 3/16	4 9/16	Y	2	2 5/8	NA	2,A	4,E,G	78	96	15-15	9'6"	3	X	350
	7539	A-	C	B	C-	B-	A-	C	B+	C	A	C	A-	A	NA	10,13,16,19,21	P	1 3/16	3 15/32	Y	2	2 7/8	6	2,A	4,E,G,W	80	96	17-8	10'	3	X	370
TRITON	TRA001	A-	A-	A	A	B-	A	C+	B-	B-	NA	A	C	A	B	8-20	P	3 5/32	3 5/32	N	1	2 1/2	2	2,4,D,E,W	A,D,G	72	92	14-3	6'6"	1	T	250

1. **A** Excellent
B Good
C Fair
NA Not available or applicable on this model

2. (F) Fixed
(P) Plunge

3. (*) For use with optional proprietary guide bushings

4. (1) Spindle lock and one wrench
(2) 2 wrenches

5. (2) 1/2" collet
(4) 1/4" collet or adapter
(A) Subbase/adaptor for guide bushings
(C) Centering cone
(D) Dust-collection hood
(E) Edge guide
(G) Guide bushings
(S) Additional subbases
(W) Depth-adjustment wrench/extension

6. (C) China
(G) Germany
(I) Italy
(J) Japan
(M) Malaysia
(T) Taiwan
(X) Mexico

7. Prices current at time of article production and do not include shipping, where applicable.