

17-19" Bandsaws from \$1,350 to \$2,300

MANUFACTURER/ MODEL	PERFORMANCE RATINGS (1)										MOTOR (2)			BLADE		CUT CAPACITIES, INCHES		TABLE			BLADE GUIDES			Type of Blade Brake (5)	Weight, Pounds	Power Cord Length, Inches (6)	Warranty, Years	Country of Assembly (7)	Selling Price (8)	
	PRIMARY					SECONDARY					Voltage	Amperage	Rated Horsepower	Length, Inches	Width (Min., Max.), Inches	Maximum Resaw Height	Maximum Width (Throat)	Dimensions (Width x Depth), Inches	Height From Floor, Inches	Max. Tilt Range (Right/Left), Degrees	Style (3)	Thrust Bearing (3)	Tool-Free Adjustments? (Yes/No) (4)							
	Power	Absence of Blade Deflection	Ease of Adjusting Blade Guides	Curve-Cutting Accuracy	Ease of Changing Blades	Ease of Tensioning Blade	Absence of Vibration	Absence of Blade Drift	Ease of Tilting and Locking Table	Rip-Fence Effectiveness																				Miter-Gauge Effectiveness
GENERAL INTERNATIONAL 90-240M1	B+	A	B	B	B	A	B	A	B-	C+	C	110*/220	15*/7.5	2	131½	⅛, 1	12	16¼	23⅝ × 17	37½	45/4	D	B	N	N	350	79	2	T	\$2,200
GRIZZLY G0513X2BF	A	A	B	B	B	B	C	A	B	B-	B	220	10	2	131½	⅛, 1	12	16¼	23⅝ × 17½	37½	46/6	D	B	N	E, F	356	N/A	1	T	\$1,350
GRIZZLY G0514X2B	A	A	B	B	B	B	C	A	A	B-	B	220	12	3	143	⅛, 1¼	12	18¼	27 × 19½	37½	48/6	D	B	N	E	427	77	1	T	\$1,725
JET JWBS-18QT-3	A	A	A	B+	B-	B+	B+	A	C-	B	C	230	13	3	137	⅛, 1½	12½	18⅝	19 × 19	37½	45/15	D	B	Y	N	415	75*	5	T	\$1,940
RIKON 10-346	A-	B	B-	A	A	B+	B	B	A-	B	NA	220	16	4	162	¼, 1⅜	19¼	17⅝	24¾ × 19	33½	45/5	E	E	Y*	F	500	129*	5	C	\$2,300
SHOP FOX W1729	A	A	C	A	B	B	A	A	B	C	B	115/230*	20/10*	2	143	⅛, 1	12¼	18¼	27 × 19½	37½	45/8	E	B	Y*	N	367	78	2	T	\$1,970

1. A Excellent B Good C Fair
- D Poor NA Not applicable

2. (*) Prewired
3. (B) Single ball bearing
(D) Dual ball bearing
(E) European discs

4. (*) Some guides do; others do not
5. (E) Electronic
(F) Foot-activated
(N) No brake

6. (N/A) Does not come with a cord
(*) Does not include a plug
7. (C) China
(T) Taiwan

8. Prices current at time of article production and do not include shipping, where applicable.