

Tricked-out 14" bandsaws deliver the goods

MODEL	PERFORMANCE RATINGS (1)											BODY STYLE (2)	BLADE SPEEDS, FEET PER MINUTE	RATED MOTOR HORSEPOWER	BLADE, INCHES		CUT CAPACITIES, INCHES		TABLE			BLADE GUIDES		ACCESSORIES (5)		OVERALL DIMENSIONS, INCHES (W x D x H)	DUST-COLLECTION PORT(S) DIAMETER, INCHES	WEIGHT, POUNDS	POWER CORD LENGTH, INCHES	WARRANTY, YEARS	COUNTRY OF ASSEMBLY (6)	SELLING PRICE (7)	CONTACT INFORMATION	
	PRIMARY					SECONDARY									LENGTH	WIDTH (MIN., MAX.)	MAXIMUM RESAW HEIGHT	MAXIMUM CUT LEFT OF BLADE	WIDTH x DEPTH, INCHES	HEIGHT FROM FLOOR, INCHES	TILT RANGE, DEGREES (RIGHT, LEFT)	NUMBER OF TRUNNIONS	SIDE GUIDES (3)	THRUST BEARINGS (4)	STANDARD									OPTIONAL
	OBSERVED POWER	CURVE-CUTTING ACCURACY	ABSENCE OF BLADE DEFLECTION	EASE OF ADJUSTING BLADE GUIDES	EASE OF CHANGING BLADES	EASE OF ADJUSTING BLADE TENSION	EASE OF ADJUSTING BLADE TRACKING	EASE OF TILTING AND LOCKING TABLE	RIP-FENCE EFFECTIVENESS	MITER-GAUGE EFFECTIVENESS	DUST-COLLECTION EFFECTIVENESS																							
GRIZZLY G0555XH	B+	A	A	B+	A	C	B-	B	A	B	B	C	3,000	1¼	105	½-¾	12¼	13¾	21¾x16½	44	50/5	2	B	C	C, F, L, M		26x31x74	1@4"	276	68	1	T	\$1,475	800-523-4777, grizzly.com
GRIZZLY G0817	A	A	A	A	A	A	A	A	A	B	A	S	2,820	2	120	½-¾	14¼	13¾	21¾x16	37	45/10	1	B	F	C, F, M	L	29x32½x76	2@4"	319	76	1	T	\$1,695	800-523-4777, grizzly.com
JET JWBS-14SFX	A	A	B	B-	B-	A-	A	B	A	N/A	A	S	3,000	1¼	116	½-¾	13¾	13½	21½x17¼	40½	48/6	1	B	C	F	L, M, P	37x27½x75½	2@4"	272	95	5	C	\$1,300	800-274-6848, jettools.com
JET JWBS-14DXPRO	B-	A	B+	B+	B	B	B-	B	N/A	N/A	C	C	1,500/3,000	1¼	105	½-¾	12¼	13¾	15x15	43¾	45/10	2	B	C	C	F, M	26¾x29x72¾	1@4"	247	70	5	T	\$1,300	800-274-6848, jettools.com
POWERMATIC PWBS-14CS	B-	A	C	B+	A-	B-	B-	B	C	B	C	C	3,000	1½	105	½-¾	12¼	12¼	20½x15	44	50/14	2	B	C	F, L, M		30x20x74½	1@4"	250	72	5	T	\$1,400	800-274-6848, powermatic.com
RIKON 10-326	B	A	B	B-	B+	A	A	A	A-	N/A	A	S	1,445/2,950	1¼	111	½-¾	13¼	13¾	21½x15¾	40%	45/6	1	B	C	C, F, P	M	29x25¾x75	1@4"	285	79	5	C	\$1,500	877-884-5167, rikontools.com
SHOP FOX W1849	A	A	A	A-	A	A	A	B+	A	N/A	A	S	2,820	2	120	½-¾	14½	13¾	21¾x16½	37	45/10	1	D	F	C, F	B, M, P	27½x32x76	2@4"	347	95	2	T	\$1,827	800-840-8420, shopfox.biz

1. **A** Excellent **B** Good **C** Fair **D** Poor **N/A** Not applicable
2. (C) Cast-iron C-frame (S) Steel-framed cabinet
3. (B) Bearings (D) Discs
4. (C) Blade contacts circumference of bearing (F) Blade contacts face of bearing
5. (B) Bearing blade-guide kit (C) Storage cabinet in base (F) Rip fence (L) Task light (M) Miter gauge (P) Pushstick
6. (C) China (T) Taiwan
7. Prices current at time of article production and do not include shipping, where applicable.