

STEP-UP TABLESAWS AFFORD GOOD OPTIONS

BRAND	MODEL	PERFORMANCE RATINGS (1)													MOTOR		DIMENSIONS, INCHES		CAPACITIES, INCHES								ACCESSORIES (3)		WEIGHT, LBS	WARRANTY, YEARS	COUNTRY OF ASSEMBLY (4)	SELLING PRICE (5)	
		PRIMARY					SECONDARY								RATED HORSEPOWER	VOLTAGE (PREWIRED IN BOLD)	OVERALL, W × D × H	TABLETOP, W × D	FRONT OF TABLE TO BLADE (2)	MAX. RIP, LEFT OF BLADE	MAX. RIP, RIGHT OF BLADE	MAX. CUTTING HEIGHT AT 90°	MAX. CUTTING HEIGHT AT 45° BEVEL	MAX. DADO WIDTH WITH ARBOR WASHER	MAX. DADO WIDTH WITHOUT ARBOR WASHER	BLADE CHANGES: 1 OR 2 WRENCHES	DUST PORT DIAMETER, INCHES	STANDARD					OPTIONAL
		OBSERVED POWER	ABSENCE OF RIP FENCE DEFLECTION	QUALITY OF MITER GAUGE	CUT QUALITY WITH PREMIUM BLADE	EASE OF USING BLADE GUARD/RIVING KNIFE	ABSENCE OF VIBRATION	EASE OF CHANGING BLADES	EASE OF USING ON/OFF SWITCH	EASE OF ALIGNING BLADE WITH MITER SLOTS	EASE OF ADJUSTING BEVEL STOPS	EASE OF SETTING BEVEL ANGLE	DUST COLLECTION	EASE OF USING HANDWHEELS																			
CRAFTSMAN	22116	C	A-	B-	B	B	A	B	B	A	A	C	A-	B+	1¾	110/220	59×64×34	40¼×27	12	12	30	3⅝	2¼	1⅜	2⅝	2	4	B	D	432	1	C	\$1,100
GENERAL INTERNATIONAL	50-090RCM1	B	A-	B-	B	B	C	B-	B-	B	A	B	B	B+	2	110/220	38×66½×42½	40×25¼	9	8	36	¾	2⅝	¾	2⅝	2	2½	B	D,M,P	217	2	T	1,000
	50-200RM1	A	A-	B	A-	A	A	B-	B-	A	C	B	A-	A	2	220	44×61×36	44×27	10¼	8	30	3	2¼	1⅜	2⅝	1	4	B	D,M,P	321	2	T	1,250
GRIZZLY	G0715P	A	A	C	A-	B	A	B	B	B	C	C	A-	A-	2	220	44×60×34	40×27	11½	12	30	3⅝	2⅝	1⅜	2⅝	1	4	B	D,M,P	393	1	C	795
JET	JPS-10TS-30	B	A	B+	A-	B	B	A	B	B	A	C	A	A-	1¾	110/220	40×60×41	44×27	10⅝	8	30	3⅝	2⅝	1⅜	2⅝	1	4	B	D,M	252	5	T	1,200
STEEL CITY	35990C	B	A-	B-	A-	C	A	B	B	A	C	B	A	B+	1½	110/220	38×68×35½	40×27	12½	20½	30¼	3⅝	2¼	¾	1⅜	2	4	B,M,P	D	328	2	C	800

1. **A** Excellent **B** Good **C** Fair
 2. Measured with blade at full height.
 3. (B) 10" 40-tooth blade (D) Dado insert (M) Mobile base (P) Pushstick
 4. (C) China (T) Taiwan
 5. Prices current at time of article production and do not include shipping, where applicable.