

MODEL	PERFORMANCE RATINGS (1)															
	POWER	EASE OF CHANGING BITS	EASE OF CHANGING BASES	FIXED BASE					PLUNGE BASE							
				EASE OF SETTING BIT DEPTH	DEPTH SCALE EASE OF USE	EASE OF USING ON/OFF SWITCH	ROUTER TABLE USE	SUBBASE VERSATILITY	DUST COLLECTION	PLUNGE SMOOTHNESS	RELIABILITY OF PLUNGE-LEVER LOCK	EASE OF USING DEPTH STOP AND TURRET	EASE OF USING DEPTH SCALE	EASE OF USING ON/OFF SWITCH	SUBBASE VERSATILITY	DUST COLLECTION
BOSCH 1617EVSPK	B	A	B	B	A	B	A	A-	NA	A	A	A	B	B	B+	NA
BOSCH MRC23EVSK	A	A	A	B	A	A	A	A-	NA	A	A	A	B	A	B+	NA
DEWALT DW616PK	B	B	B	B	B	B	B	C	NA	A	B	B	B	B	B	A
DEWALT DW618PK	A	B	B	B	B	B	B	A	NA	A	B	B	B	B	A	A
HERCULES HE041	C	A	B	B	A	B	A-	A	A-	A	B	D	B	B	A	A-
MAKITA RF1101KIT2	C	C	B	B	A	C	B-	A	NA	A	A	C	B	C	A	NA
METABO HPT KM12VC	C	A	B	B	B	D	B-	B	NA	B	A	C	C	D	B	NA
MILWAUKEE 5616-24	A	A	A	A	A	A-	B	B	A	A	A	A	A	A-	B	A
SKIL RT1322-00	B	A	B	B	B	B	B	C	A-	A	B	D	B	B	C	A-

1. **A** Excellent
B Good
C Fair
D Poor
NA Not applicable

2. **(L)** Spindle lock and one wrench
(2) 2 wrenches
3. **(*)** Requires optional wrench, sold separately
4. **(A)** Subbase adapter for guide bushings
(C) Centering cone
(D) Dust-collection hood

MOTOR				BASE SPECIFICATIONS								ACCESSORIES (4)		WEIGHT			
SPEED RANGE (MIN.-MAX.), RPM × 1,000	RATED HORSEPOWER	RATED AMPERAGE	COLLET-TIGHTENING METHOD (2)	FIXED BASE				PLUNGE BASE				STANDARD (4)	OPTIONAL (4)	IN FIXED BASE	IN PLUNGE BASE	NOISE LEVEL AT MAX. RPM, NO LOAD	WARRANTY
				SUBBASE OPENING	BASE OPENING (W/O SUBBASE)	MAX. COLLET TRAVEL	THROUGH-TABLE ADJUSTMENT? (3)	SUBBASE OPENING	BASE OPENING (W/O SUBBASE)	MAX. PLUNGE DEPTH	NUMBER OF TURRET DEPTH STOPS						
8-25	2.25	12	2	2 1/16"	3 3/4"	1 7/16"	✓	2 1/16"	3 5/16"	2 1/4"	7	W	A,C,D,E,F,G	8.6 lbs	10.0 lbs	98 dB	1 year
10-25	2.3	15	2	2 1/16"	4"	1 7/16"	✓	2 1/16"	3 5/16"	2 3/16"	7	W,L	A,C,D,E,F,G	9.9 lbs	12.6 lbs	101 dB	1 year
24.5	1.75	11	2	1 3/16"	3 3/4"	1 1/2"		1 3/16"	3 9/16"	2 5/16"	5	C,D	E,S	8.1 lbs	10.9 lbs	102 dB	3 years
8-24.5	2.25	12	L	1 3/16"	3 3/4"	1 1/2"		1 3/16"	3 9/16"	2 5/16"	5	D**,S	E	8.3 lbs	11.1 lbs	100 dB	3 years
10-25	2.25	12	L	1 3/16"	3 5/8"	2 1/16"	✓*	1 3/16"	3 1/4"	2 5/16"	4	D,E,L,S	NA	7.8 lbs	9.1 lbs	102 dB	90 days
8-24	2.25	11	2	1 3/16"	3 7/16"	2"		1 3/16"	3 7/16"	2 5/8"	3	S	D,E,G	8.0 lbs	9.9 lbs	96 dB	1 year
8-24	2.25	11	2	1 3/4"	3 3/8"	2"		1 3/4"	3 7/16"	2 1/2"	3	A,G,S	D,E	8.1 lbs	10.7 lbs	96 dB	5 years
10-24	2.25	13	2	2 1/2"	3 5/16"	1 3/8"	✓	1 3/16"	3 1/4"	2 7/8"	6	C,D,W	NA	8.4 lbs	11.6 lbs	99 dB	5 years
10-25	2.25	12	L	1 3/16"	3 5/8"	2 1/16"	✓*	1 3/16"	3 1/4"	2 5/16"	4	D,E,L	NA	8.4 lbs	9.8 lbs	102 dB	90 days

- (D**)** Dust collection only on plunge base
(E) Edge guide
(F) Fine-adjustment extension handle
(G) Guide bushings
(H) D-handle base
(L) LED task lights
(S) Extra subbases
(W) Router-table depth-adjustment wrench

5. Prices current at time of article production and do not include shipping, where applicable.